

型式 Model	注 Note	Type	d	D	D ₁	L	L ₁	L ₂	ℓ	ℓ ₁	ℓ ₂	d ₁	L ₀	G P=1.0	Max. min ⁻¹	kg	—	スパナ Spanner
BT30 -CT16SA - 75		1	16	45	—	75	—	—	65	—	15	—	—	M10	16,000	0.9		HS-1-16
- 90		1	16	45	—	90	—	—	65	—	15	—	—	M10	16,000	1.1		
-CT20SA - 75	*1	2	20	52	—	75	—	—	65	—	15	—	★ 27	M12	15,000	1.0		
- 90		2	20	52	—	90	—	—	80	—	15	—	40	M12	14,000	1.2		HS-2-20
- 105		2	20	52	—	105	—	—	80	—	15	—	55	M12	12,000	1.3		
-CT25SA - 90		2	25	61	—	90	—	—	80	—	15	—	★ 31	M12	11,000	1.4		HS-2.5-25
- 105		2	25	61	—	105	—	—	80	—	15	—	44	M12	10,000	1.6		
-CT32SA - 90	*1	2	32	68	—	90	—	—	68	—	20	—	★ 30	M18	8,000	1.6		HS-3-32
BT40 -CT16SA - 75		1	16	45	—	75	—	—	65	—	15	—	—	M10	20,000	1.4		HS-1-16
- 90		1	16	45	—	90	—	—	65	—	15	—	—	M10	20,000	1.6		
-CT20SA - 75		1	20	52	—	75	—	—	75	—	15	—	—	M12	18,000	1.5		
- 90		1	20	52	—	90	—	—	80	—	15	—	—	M12	18,000	1.8		HS-2-20
- 105		1	20	52	—	105	—	—	80	—	15	—	—	M12	18,000	2.1		
- 120		1	20	52	—	120	—	—	80	—	15	—	—	M12	18,000	2.3		
-CT25SA - 90		1	25	61	—	90	—	—	80	—	15	—	—	M12	16,000	2.0		
- 105		1	25	61	—	105	—	—	80	—	15	—	—	M12	16,000	2.3		HS-2.5-25
- 120		1	25	61	—	120	—	—	80	—	15	—	—	M12	16,000	2.7		
- 135		1	25	61	—	135	—	—	80	—	15	—	—	M12	14,000	3.0		
-CT32SA - 90		2	32	73	—	90	—	—	76	32	17	26	★ 31	M18	12,000	2.3		
- 105		2	32	73	—	105	—	—	85	23	17	26	44	M18	12,000	2.5		HS-3-32
- 120		2	32	73	—	120	—	—	85	23	17	26	59	M18	12,000	2.9		
- 135		2	32	73	—	135	—	—	120	—	17	—	74	M18	12,000	3.2		

型式 Model		注 Note	Type	d	D	D ₁	L	L ₁	L ₂	ℓ	ℓ ₁	ℓ ₂	d _i	L0	G P=1.0	Max. min ⁻¹	kg	—	スパナ Spanner
BT50	-CT16SA - 90		3	16	45	58	90	7	45	65	—	20	—	—	M10	15,000	4.1	HS-1-16	
	- 105		3	16	45	70	105	22	45	65	—	20	—	—	M10	15,000	4.4		
	- 135		3	16	45	70	135	52	45	65	—	20	—	—	M10	15,000	5.0		
-CT20SA - 90			3	20	52	65	90	7	45	80	—	15	—	—	M12	15,000	4.2	HS-2-20	
- 105			3	20	52	70	105	9	58	80	—	15	—	—	M12	15,000	4.5		
- 120			3	20	52	70	120	24	58	80	—	15	—	—	M12	15,000	4.9		
- 135			3	20	52	73	135	39	58	80	—	15	—	—	M12	14,000	5.4		
- 165			3	20	52	73	165	69	58	80	—	15	—	—	M12	13,000	6.1		
- 200			3	20	52	73	200	104	58	80	—	15	—	—	M12	12,000	6.8		
- 250			3	20	52	73	250	154	58	80	—	15	—	—	M12	10,000	7.9		
- 300			3	20	52	73	300	204	58	80	—	15	—	—	M12	7,000	9.3		
-CT25SA - 105			3	25	61	82	105	11	56	80	—	15	—	—	M12	14,000	4.8		HS-2.5-25
- 120			3	25	61	82	120	26	56	80	—	15	—	—	M12	13,000	5.2		
- 135			3	25	61	83	135	41	56	80	—	15	—	—	M12	12,000	5.7		
- 165			3	25	61	86	165	71	56	80	—	15	—	—	M12	11,000	6.6		
- 200			3	25	61	86	200	106	56	80	—	15	—	—	M12	10,000	7.7		
- 250			3	25	61	86	250	156	56	80	—	15	—	—	M12	9,000	9.2		
- 300			3	25	61	86	300	206	56	80	—	15	—	—	M12	8,000	10.8	HS-3-32	
-CT32SA - 95			1	32	73	—	95	—	—	120	—	20	—	—	M18	12,000	4.6		
- 105			1	32	73	—	105	—	—	120	—	20	—	—	M18	12,000	4.9		
- 120			3	32	73	87	120	26	56	120	—	20	—	—	M18	12,000	5.6		
- 135			3	32	73	88	135	41	56	120	—	20	—	—	M18	12,000	6.2		
- 150			3	32	73	87	150	56	56	120	—	20	—	—	M18	11,000	6.7		
- 165			3	32	73	86	165	71	56	120	—	20	—	—	M18	10,000	7.2		
- 200			3	32	73	88	200	106	56	120	—	20	—	—	M18	9,000	8.6		
- 250			3	32	73	88	250	156	56	120	—	20	—	—	M18	8,000	10.5		
- 300			3	32	73	88	300	206	56	120	—	20	—	—	M18	7,000	12.4	HS-4-42	
-CT42SA - 95			1	42	88	—	95	—	—	120	—	20	—	—	M18	10,000	5.0		
- 105			1	42	88	—	105	—	—	120	—	20	—	—	M18	10,000	5.4		
- 120			1	42	88	—	120	—	—	120	—	20	—	—	M18	10,000	6.1		
- 135			1	42	88	—	135	—	—	120	—	20	—	—	M18	10,000	6.8		
- 150			1	42	88	—	150	—	—	120	—	20	—	—	M18	10,000	7.4		
- 165			1	42	88	—	165	—	—	120	—	20	—	—	M18	9,000	8.1		
- 200			1	42	88	—	200	—	—	120	—	20	—	—	M18	8,000	9.7		
- 250			1	42	88	—	250	—	—	120	—	20	—	—	M18	7,000	12.0		
- 300			1	42	88	—	300	—	—	120	—	20	—	—	M18	6,000	14.2		